




SCHEMA ELECTRIQUE
VUE DE DESSUS



POUSOIR NOIR

BLACK BUTTON

COMMUNS SEPARES

SEPARAT COMMONS

ENDURANCE MECANIQUE: 100000 CYCLES

MECHANICAL STRENGTH: 100000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-452-501

HOMOLOGUATION

83452516
Product:

FICHE EQUIPEMENT AIR / AIR EQUIPEMENT SHEET	6.536.120
SAAB	S9307061-001

C	CTP 5020 : MISE A JOUR SCHMME ELECTRIQUE SUIVANT SPEC SAAB INDICE D	Modified by	F_MONCHIAL	09/09/2002
	AJOUT REFERENCE SPECIF SAAB DANS LE TABLEAU	Verified by	R_JUNILLON	09/09/2002
		Authorized by		

Toler. gene. lin ± mm
Toler. gene. Ang ± degres



General Raw surface Ra ✓

This document is the property of Crouzet-Automatismes.
It's contents cannot be reproduced or divulged without the company's written approval.
The product data and specifications found on this document do not constitute any contractual obligation.
Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
All rights of reproduction, modification, reprinting, and translation reserved for all countries.



Scale **1/1**

Customer: SAAB		Customer Ref.:	
Designation/FR: BOUTON 4 DIRECTIONS ETANCHE A EFFET TACTILE - CONTACTEUR		PFT001 : x<C>;y<M>	
Designation/GB: WATERPROOF FOR WAYS BUTTON WITH TACTILE EFFECT - NORMALLY OPEN		Dispatching 01	
Department:	Design by R_JUNILLON 17/03/1995	N°REV	Format
NATO code: FA0X2	Verif. by M_DOREY 17/03/1995	C	A4
	Authorized by	Folio 1/1	
FT83452516FR			