


POUSSOIR BLEU
 ENDURANCE MECANIQUE : 100 000 cycles
 ETANCHEITE FACE AVANT SUIVANT :
 MIL STD 810 D-506.2 Methode 2
 AUTRES CARACTERISTIQUES, IDENTIQUES A :

BLUE BUTTON
 MECHANICAL STRENGTH : 100 000 cycles
 WATERPROOF FRONT FACE IN COMFORMITY WITH :
 MIL STD 810 D-506.2 Methode 2
 other characteristics identical to /

FT83452501FR

SCALE 1/1



-
-
83452542
Product:

B	CTP 9370: 10.6±0.6-→10.8±0.5		Modified by	D_DELIAUD	20/04/2010
			Verified by	F_MATTANA	20/04/2010
		Authorized by		NON APPLIC.	
Toler. gene. lin ± mm		This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.			
Toler. gene. Ang ± degrees					
	General Raw surface	Ra	Scale 1/1		
	Customer: HAL		Customer Ref.:		
2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France		Designation/FR: TRIM 4D UNIPOLAIRE EFFET TACTILE CONTACTEUR ETANCHE		PFT001:0<C>;0<M>	
		Designation/GB: WATERPROFF 4 WAYS BUTTON WITH TACTILE EFFECT NORMALLY OPEN		Dispatching 01	
Department: CT		Design by F_MONCHAL 01/02/2006		FICHE TECHNIQUE - DATA SHEET	
		Verif. by A_BONNARD 01/02/2006		Index Format Folio	
NATO code: FA0X2		Authorized by NON APPLIC.		FT83452542FR B A4 1/1	