



CONTACTS : ARGENT + FLASH OR 5 μ

CONTACTS : SILVER + GOLD PLATED 5 μ

BAS NIVEAU

LOW CURRENT

TENSION	30 VDC	115 VAC 400 Hz	VOLTAGE
COURANT	0.5 mA à 50 mA	0.5 mA à 50 mA	CURRENT
ENDURANCE ELECTRIQUE PAR DIRECTION	100 000 cycles	100 000 cycles	ELECTRICAL LIFE PER DIRECTION

TEMPS DE REBOND : < 25 ms

BOUNCE TIME : < 25 ms

AUTRES CARACTERISTIQUES, IDENTIQUES A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83452701FR

-
83452706
Product:

A	CT 2541 : CREATION DE L'OBJET	Modified by	F_MONCHAL	27/11/2007
	IA 2007063	Verified by	A_BONNARD	27/11/2007
		Authorized by	NON APPLIC.	

Toler. gene. lin ±	mm	<p>This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries</p>	
Toler. gene. Ang ±	degrees		
Crouzet	General Ra ✓ Raw surface		Scale 1/1

2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France	Customer:	Customer Ref.:	PFT001:x<C>;y<M>		
	Designation/FR: TRIM 4D + VALIDATION, TYPE CONTACTEUR, ETANCHE, POUSSOIR SAPIN	Designation/GB: WATERPROOF FOUR WAYS BUTTON, NORMALLY OPEN		Dispatching	D1
Department: CT	Design by F_MONCHAL 27/11/2007	DATA SHEET			Index
NATO code: FA0X2	Verif. by A_BONNARD 27/11/2007	FT83452706FR			Format
	Authorized by NON APPLIC.				Folio
					A A4 1/1