



CARACTERISTIQUES ELECTRIQUES
ELECTRICAL CHARACTERISTICS

TENSION	28 Vdc	VOLTAGE
COURANT	0.1 mA à 500 mA	CURRENT
ENDURANCE ELECTRIQUE	100 000 cycles	ELECTRICAL LIFE

Autres caractéristiques identiques à : FT83452701FR
Other characteristics identical to :

-
83452719
Product:

A	CREATION DE L'OBJET	Modified by	T_VINARD	10/02/2011
		Verified by	P_GIROUD	10/02/2011
		Authorized by	NON APPLIC.	

Toler. gene. lin ± 0.1 mm	<p>This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries</p>	
Toler. gene. Ang ± 3 degrees		
	General Raw surface Ra ✓	Scale 1/1

2, rue du Dr ABEL BP 59, 26902. Valence CEDEX 9 France	Customer:	Customer Ref.:	PFT001:x<C>;y<M>		
	Designation/FR: TRIM 4D + VALID ETANCHE CT DORE Designation/GB: 4 WAY WATERPROOF BUTTON TACTILE EFFECT + PUSH BUTTON LOW CURRENT	DATA SHEET FT83452719FR		Dispatching	D1
Department: CT	Design by T_VINARD 10/02/2011 Verif. by P_GIROUD 10/02/2011	Index Format Folio A A4 1/1			
NATO code: FA0X2	Authorized by NON APPLIC.				