



Poussoir : Noir  
 Button : Black  
 Endurance mécanique : 100000 Cycles  
 Mechanical strenght  
 Etanchéité face avant suivant : MIL STD 810 D-506.2 METHODE 2  
 Waterproff front face according to

CARACTERISTIQUES ELECTRIQUES  
ELECTRICAL CHARACTERITICS

TENSION	28 Vdc	VOLTAGE
COURANT	0.1 mA à 500 mA	CURRENT
ENDURANCE ELECTRIQUE	100 000 cycles	ELECTRICAL LIFE

Autres caractéristiques identiques à : FT83450702FR  
 Other characteristics identical to :

-
83450732
Product:

<b>A</b>	CREATION DE L'OBJET	Modified by	T_VINARD	03/06/2010
		Verified by	P_GIROUD	03/06/2010
		Authorized by	NON APPLIC.	

Toler. gene. lin ±	0.1	mm	This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries	
Toler. gene. Ang ±	3	degrees		
	General Raw surface $R_a$ ✓			Scale <b>1/1</b>

2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France	Customer:	Customer Ref.:	PFT001: x<C>;y<M>			
	Designation/FR:	<b>BOUON POUSSOIR UNIPOLAIRE ETANCHE NOIR CT DORE</b>		Dispatching <b>DI</b>		
	Designation/GB:	<b>BLACK WATERPROOF PUSH-BUTTON TACTILE EFFECT LOW CURRENT</b>		Index	Format	Folio
	Department:	Design by T_VINARD 03/06/2010	<b>DATA SHEET</b>		A	A4
CT	Verif. by P_GIROUD 03/06/2010	<b>FT83450732FR</b>				
NATO code: FA0X2	Authorized by NON APPLIC.					