



POUSSOIR NOIR

BLACK BUTTON

ENDURANCE MECANIQUE: 100000 CYCLES

MECHANICAL STRENGTH: 100000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-450-001

SPECIFIC ELECTRICAL CHARACTERISTICS	
VOLTAGE 28VCC	
INDUCTIVE L/R 5ms	ELECTRICAL ENDURANCE
I ≤ 2A ->	100 000 CYCLES
I ≤ 2.5A ->	80 000 CYCLES
I ≤ 3.5A ->	50 000 CYCLES

-  
-  
83450006

Product:

CTP 5214 : AJOUT DIAM 14 ET COTE 3.1 MAX

Modified by	F_MONCHIAL	08/04/2002
Verified by	R_JUNILLON	08/04/2002
Authorized by		



Toler. gene. lin ±  
Toler. gene. Ang ±

mm  
degrees

General Ra  
Raw surface

2, rue du Dr. ABEL  
BP 59, 26902,  
Valence CEDEX 9  
France

Department:  
CT

NATO code: FA0X2

Customer:  
Designation/FR: **BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR UNIPOLAIRE**  
Designation/GB: **WATERPROOF PUSH-BUTTON TACTILE-EFFECT SINGLE POLE CHANGE OVER**  
Design by R\_JUNILLON 12/04/1996  
Verif. by C\_MARTIN 12/04/1996  
Authorized by

Customer Ref.:

PF001:0<C>;0<M>  
Dispatching **01**

**FT83450006FR**  
Index **B** Format **A4** Folio **1/1**

DATA SHEET



This document is the property of Crouzet-Automatismes.  
It's contents cannot be reproduced or divulged without the company's written approval.  
The product data and specifications found on this document do not constitute any contractual obligation.  
Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.  
All rights of reproduction, modification, reprinting, and translation reserved for all countries.

Scale **1/1**