



POUSSOIR ROUGE

RED BUTTON

ENDURANCE MECANIQUE: 100000 CYCLES

MECHANICAL STRENGTH: 100000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-450-001

SPECIFIC ELECTRICAL CHARACTERISTICS

VOLTAGE 28VCC	
INDUCTIVE L/R 5ms	ELECTRICAL ENDURANCE
I ≤ 2A ->	100 000 CYCLES
I ≤ 2,5A ->	80 000 CYCLES
I ≤ 3,5A ->	50 000 CYCLES

-  
-  
83450007  
Product:

CTP 5214 : AJOUT DIAM 14 ET COTE 3.1 MAX

Modified by F-MONCHAL 08/04/2002  
Verified by R-JUNILLON 08/04/2002  
Authorized by



2, rue du Dr. ABEL  
BP 59, 26902,  
Valence CEDEX 9  
France

Department:

CT

NATO code: FA0X2

Toler. gene. lin ±  
Toler. gene. Ang ±

mm  
degres

General  
Raw surface



Customer:

Customer Ref.:

Designation/FR:

**BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR UNIPOLAIRE**

Designation/GB:

**WATERPROOF PUSH-BUTTON TACTILE-EFFECT SINGLE POLE CHANGE OVER**

Design by R-JUNILLON 12/04/1996

Verif. by C-MARTIN 12/04/1996

Authorized by



Scale  
**1/1**

*This document is the property of Crouzet-Automatismes.  
It's contents cannot be reproduced or divulged without the company's written approval.  
The product data and specifications found on this document  
do not constitute any contractual obligation.  
Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.  
All rights of reproduction, modification, reprinting, and translation reserved for all countries.*

PFT001:0<C>;0<M>

Dispatching **01**

Index **B**

Format **A4**

Folio **1/1**

DATA SHEET

**FT83450007FR**