



POUSSOIR ROUGE

ENDURANCE MECANIQUE: 100000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

RED BUTTON

MECHANICAL STRENGTH: 100000 CYCLES

WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-450-001

-
-
83450011
Product:

A	CTP 5214 : CORRECTION COTE 2.1 MAX DEVIENT 3.1 MAX		
	Modified by	F_MONCHIAL	09/04/2002
	Verified by	R_JUNILLON	09/04/2002
Authorized by			

Toler. gene. lin ± mm
Toler. gene. Ang ± degres



General
Raw surface



2, rue du Dr. ABEL
BP 59, 26902,
Valence CEDEX 9
France

Department:

CT

NATO code: FA0X2

Customer:

Designation/FR:

Designation/GB:

Design by

Verif. by

Authorized by

Customer Ref.:

BOUTON POUSSOIR COURT ETANCHE A EFFET TACTILE INVERSEUR UNIPOL

WATERPROOF SHORT PUSH-BUTTON TACTILE-EFF SINGLE POLE CHANGE OVER

DATA SHEET

FT8345001FR



Scale

1/1

*This document is the property of Crouzet-Automatismes.
It's contents cannot be reproduced or divulged without the company's written approval.
The product data and specifications found on this document
do not constitute any contractual obligation.
Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
All rights of reproduction, modification, reprinting, and translation reserved for all countries.*

PFT001:0<C>;0<M>

Dispatching

Index

Format
A A4

Folio

1/1