



POUSSOIR NOIR

BLACK BUTTON

ENDURANCE MECANIQUE: 100000 CYCLES

MECHANICAL STRENGTH: 100000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-450-001

SPECIFIC ELECTRICAL CHARACTERISTICS	
VOLTAGE 28VCC	
INDUCTIVE L/R 5ms	ELECTRICAL ENDURANCE
I ≤ 2A ->	100 000 CYCLES
I ≤ 2.5A ->	80 000 CYCLES
I ≤ 3.5A ->	50 000 CYCLES

-
-
83450013
Product:

CREATION

Modified by	R_JUNILLON	21/06/2002
Verified by	F_MONCHAL	21/06/2002
Authorized by		

Toler. gene. lin ±

mm

Toler. gene. Ang ±

degres



General
Raw surface

Ra



2, rue du Dr. ABEL
BP 59, 26902,
Valence CEDEX 9
France

Customer: HAL

Department: CT

Designation/FR: BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR UNIPOLAIRE

NATO code: FA0X2

Designation/GB: WATERPROOF PUSH-BUTTON TACTILE-EFFECT SINGLE POLE CHANGE OVER

Authorized by

Design by R_JUNILLON 21/06/2002

Verif. by F_MONCHAL 18/06/2002

Customer Ref.:

Dispatching

Index

Format

Folio

Scale
1/1

PFT001:0<C>;0<M>

FT83450013FR

A

A4

1/1