

POUSSOIR GRIS

GREY BUTTON

ENDURANCE MECANIQUE: 100 000 CYCLES

MECHANICAL STRENGTH: 100 000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

WATERPROOF FRONT FACE IN COMFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

MIL STD 810 D-506.2 METHODE 2

CARACTERISTIQUES ELECTRIQUES

ELECTRICAL CHARACTERISTICS

BAS NIVEAU


LOW CURRENT

| | | |
|------------------------------------|----------------|-------------------------------|
| TENSION | 30 VDC | VOLTAGE |
| COURANT | 0.5 mA à 50 mA | CURRENT |
| ENDURANCE ELECTRIQUE PAR DIRECTION | 100 000 cycles | ELECTRICAL LIFE PER DIRECTION |

AUTRES CARACTERISTIQUES IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83450001FR



83450015

Product:

G

CTP 6835 : Add ELECTRICAL CHARACTERISTICS TABLE
Add GREY and LOW CURRENT in designation

| | | |
|---------------|-------------|------------|
| Modified by | JL_BOURGNE | 26/09/2007 |
| Verified by | F_MONCHAL | 26/09/2007 |
| Authorized by | Non Applic. | |

Toler. gene. lin ± mm
Toler. gene. Ang ± degrees

This document is the property of Crouzet-Automatismes.
It's contents cannot be reproduced or divulged without the company's written approval.
The product data and specifications found on this document do not constitute any contractual obligation.
Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
All rights of reproduction, modification, reprinting, and translation reserved for all countries



General Ra
Raw surface ✓

Scale
1/1

2, rue du Dr ABEL
BP 59, 26902,
Valence CEDEX 9
France

Customer: Customer Ref.:

Designation/FR: **BOUTON POUSSOIR ETANCHE GRIS - INVERSEUR - BAS NIVEAU**
Designation/GB: **WATERPROOF PUSH-BUTTON GREY - CHANGE OVER - LOW CURRENT**

PFT001:0<C>;0<M>

Dispatching **D1**

Department: **CT**
Design by T_VINARD 21/09/2005
Verif. by F_MONCHAL 21/09/2005

DATA SHEET - FICHE TECHNIQUE

Index Format Folio

FT83450015GB

G A4 1/1

NATO code: FA0X2 Authorized by Non Applic.