


POUSSOIR BLEU
 ENDURANCE MECANIQUE: 100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:
 MIL STD 810 D-506.2 METHODE 2
 AUTRES CARACTERISTIQUES, IDENTIQUE A :

BLUE BUTTON
 MECHANICAL STRENGTH: 100000 CYCLES
 WATERPROOF FRONT FACE IN COMFORMITY WITH:
 MIL STD 810 D-506.2 METHODE 2
 OTHER CHARACTERISTICS IDENTICAL TO :

FT83-450-001



83450016
 Product:

A	CT 2250 : CREATION	Modified by	F_MONCHAL	13/02/2006
	IA 2004046	Verified by	A_BONNARD	13/02/2006
		Authorized by		

Toler. gene. lin ±	mm	<i>This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.</i>	
Toler. gene. Ang ±	degrees		
	General Ra ✓ Raw surface		Scale 1/1

2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France	Customer:	Customer Ref.:	PFT001:0<C>;0<M>		
	Designation/FR: BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR UNIPOLAIRE Designation/GB: WATERPROOF PUSH-BUTTON TACTILE-EFFECT SINGLE POLE CHANGE OVER	DATA SHEET - FICHE TECHNIQUE FT83450016FR		Dispatching	D1
Department: CT	Design by F_MONCHAL 13/02/2006 Verif. by A_BONNARD 13/02/2006		Index	Format	Folio
NATO code: FA0X2	Authorized by		A	A4	1/1