



POUSSOIR GRIS

ENDURANCE MECANIQUE: 100 000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

MIL STD 810 D-506.2 METHODE 2

GREY BUTTON

MECHANICAL STRENGTH: 100 000 CYCLES

WATERPROOF FRONT FACE IN COMFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

CARACTERISTIQUES ELECTRIQUES ELECTRICAL CHARACTERISTICS

BAS NIVEAU

TENSION	30 VDC	VOLTAGE
COURANT	0.5 mA à 50 mA	CURRENT
ENDURANCE ELECTRIQUE PAR DIRECTION	100 000 cycles	ELECTRICAL LIFE PER DIRECTION

LOW CURRENT

AUTRES CARACTERISTIQUES.IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83450001FR

-
83450018
Product:

<b>B</b>	CTP 9463 : AJOUT Amdt A	Modified by	C_BODIN	20/12/2010
	IA2005073	Verified by	F_MONCHAL	20/12/2010
		Authorized by	NON APPLIC.	

Toler. gene. lin ± 0.5 mm	<p>This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.</p>	
Toler. gene. Ang ± 2 degrees		
	<p>General Raw surface Ra ✓</p>	<p>Scale 1/1</p>

2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France	Customer:	Customer Ref.:	PFT001:x<C>;y<M>			
	Designation/FR:	<b>BOUTON POUSSOIR GRIS COURT ETANCHE</b>		Dispatching	<b>01</b>	
Department:	Design by F_MONCHAL 18/04/2008	<b>WATERPROOF, SHORT PUSH-BUTTON CHANGE-OVER, TACTILE-EFFECT</b>		Index	Format	Folio
CT	Verif. by O_NGOAGOUNI 18/04/2008	<b>DATA SHEET</b>		<b>B</b>	<b>A4</b>	1/1
NATO code: FA0X2	Authorized by NON APPLIC.	<b>FT83450018FR</b>				