



POUSSOIR GRIS

GREY BUTTON

ENDURANCE MECANIQUE: 100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:

MECHANICAL STRENGTH: 100000 CYCLES
 WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-450-501

| SPECIFIC ELECTRICAL CHARACTERISTICS | |
|-------------------------------------|----------------------|
| VOLTAGE 28VCC | |
| INDUCTIVE L/R 5ms | ELECTRICAL ENDURANCE |
| I ≤ 2A -> | 100 000 CYCLES |
| I ≤ 2.5A -> | 80 000 CYCLES |
| I ≤ 3.5A -> | 50 000 CYCLES |

-
 -
83450509
 Product:

CTP 5214 : AJOUT DIAM 14 ET COTE 3.1 MAX

| | | |
|---------------|------------|------------|
| Modified by | F_MONCHIAL | 09/04/2002 |
| Verified by | R_JUNILLON | 09/04/2002 |
| Authorized by | | |

Toler. gene. lin ± mm
 Toler. gene. Ang ± degres

General Ra
 Raw surface

Scale **1/1**

*This document is the property of Crouzet-Automatismes.
 It's contents cannot be reproduced or divulged without the company's written approval.
 The product data and specifications found on this document
 do not constitute any contractual obligation.
 Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
 All rights of reproduction, modification, reprinting, and translation reserved for all countries*

2, rue du Dr. ABEL
 BP 59, 26902,
 Valence CEDEX 9
 France

Customer:

Customer Ref.:

Designation/FR:

BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR UNIPOLAIRE

PFT001:0<C>;0<M>

Designation/GB:

WATERPROOF PUSH-BUTTON TACTILE-EFFECT SINGLE POLE CHANGE OVER

Dispatching **01**

Department:

Design by R_JUNILLON 23/11/1993

Index **C**

CT

Verif. by R_JUNILLON 23/11/1993

Format **A4**

NATO code: FA0X2

FT83450509FR

Folio **1/1**