



POUSSOIR ROUGE
 ENDURANCE MECANIQUE: 100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:
 MIL STD 810 D-506.2 METHODE 2

RED BUTTON
 MECHANICAL STRENGTH: 100000 CYCLES
 WATERPROOF FRONT FACE IN COMFORMITY WITH:
 MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-450-501

SPECIFIC ELECTRICAL CHARACTERISTICS	
VOLTAGE 28VCC	ELECTRICAL ENDURANCE
INDUCTIVE L/R 5ms	
$I \leq 2A \rightarrow$	100 000 CYCLES
$I \leq 2,5A \rightarrow$	80 000 CYCLES
$I \leq 3,5A \rightarrow$	50 000 CYCLES

-
 -
83450510
 Product:

B CTP 5214 : AJOUT DIAM 14 ET COTE 3.1 MAX

Modified by F_MONCHIAL 09/04/2002
 Verified by R_JUNILLON 09/04/2002
 Authorized by

Toler. gene. lin \pm mm
 Toler. gene. Ang \pm degres

General Ra
 Raw surface

Scale **1/1**

*This document is the property of Crouzet-Automatismes.
 It's contents cannot be reproduced or divulged without the company's written approval.
 The product data and specifications found on this document
 do not constitute any contractual obligation.
 Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
 All rights of reproduction, modification, reprinting, and translation reserved for all countries.*

2, rue du Dr. ABEL
 BP 59, 26902,
 Valence CEDEX 9
 France

Customer:
 Designation/FR: **BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR UNIPOLAIRE**
 Designation/GB: **WATERPROOF PUSH-BUTTON TACTILE-EFFECT SINGLE POLE CHANG OVER**

Dispatching **01**
 Index **B**
 Format **A4**
 Folio **1/1**

Department: CT
 NATO code: FA0X2

DATA SHEET
FT83450510FR