

POUSSOIR BLEU

ENDURANCE MECANIQUE: 100000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

BLUE BUTTON

MECHANICAL STRENGTH: 100000 CYCLES

WATERPROOF FRONT FACE IN COMFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-450-501

SPECIFIC ELECTRICAL CHARACTERISTICS	
VOLTAGE 28VCC INDUCTIVE L/R 5ms	ELECTRICAL ENDURANCE
I ≤ 2A ->	100 000 CYCLES
I ≤ 2,5A ->	80 000 CYCLES
I ≤ 3,5A ->	50 000 CYCLES

83450514

Product:

A

CT 2251 : CREATION
IA 2004046

Modified by	F_MONCHAL	02/02/2006
Verified by	A_BONNARD	02/02/2006
Authorized by		


Toler. gene. lin ± mm

Toler. gene. Ang ± degrees



General Ra ✓
Raw surface

This document is the property of Crouzet-Automatismes.
It's contents cannot be reproduced or divulged without the company's written approval.
The product data and specifications found on this document do not constitute any contractual obligation.
Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
All rights of reproduction, modification, reprinting, and translation reserved for all countries



Scale
1/1

2, rue du Dr ABEL
BP 59, 26902,
Valence CEDEX 9
France

Customer:

Customer Ref.:

Designation/FR: **BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR UNIPOLAIRE**

PFT001:0<C>;0<M>

Designation/GB: **WATERPROOF PUSH-BUTTON TACTILE-EFFECT SINGLE POLE CHANGE OVER**

Dispatching **01**

Department:

Design by F_MONCHAL 02/02/2006

DATA SHEET - FICHE TECHNIQUE

Index Format Folio

CT

Verif. by A_BONNARD 02/02/2006

FT83450514FR

A A4 1/1

NATO code: FA0X2

Authorized by