

ENDURANCE MECANIQUE:100 000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:
 MIL STD 810 D-506.2 METHODE 2
 AUTRES CARACTERISTIQUES.IDENTIQUE A :

MECHANICAL STRENGTH:100 000 CYCLES
 WATERPROOF FRONT FACE IN COMFORMITY WITH:
 MIL STD 810 D-506.2 METHODE 2
 OTHER CHARACTERISTICS IDENTICAL TO :

FT83-451-001



83451003

Product:


A

IA2008029 : CREATION

Modified by	M_VERDIER	28/05/2009
Verified by	F_MONCHAL	28/05/2009
Authorized by		

Toler. gene. lin ±	mm
Toler. gene. Ang ±	degrees

This document is the property of Crouzet-Automatismes.
 It's contents cannot be reproduced or divulged without the company's written approval.
 The product data and specifications found on this document do not constitute any contractual obligation.
 Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
 All rights of reproduction, modification, reprinting, and translation reserved for all countries



General Ra ✓
 Raw surface

Scale
 1/1

2, rue du Dr ABEL
 BP 59, 26902,
 Valence CEDEX 9
 France

Customer: Customer Ref.:

Designation/FR: **BOUTON POUSSOIR ETANCHE TACTILE INVERSEUR UNIPOLAIRE NOIR**
 Designation/GB: **BLACK WATERPROOF PUSH-BUTTON TACTILE SINGLE POLE CHANGE OVER**

PFT001:0<C >;0<M>

Dispatching **D1**

Department:	Design by	M_VERDIER	28/05/2009
CT	Verif. by	F_MONCHAL	28/05/2009

DATA SHEET - FICHE TECHNIQUE

Index	Format	Folio
-------	--------	-------

FT83451003FR

A	A4	1/1
----------	-----------	-----

NATO code: FA0X2 Authorized by