



POUSSOIR ROUGE

ENDURANCE MECANIQUE: 100000 CYCLES  
 ETANCHEITE FACE AVANT SUIVANT:  
 MIL STD 810 D-506.2 METHODE 2

RED BUTTON

MECHANICAL STRENGTH: 100000 CYCLES  
 WATERPROOF FRONT FACE IN CONFORMITY WITH:  
 MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-453-001

-  
 -  
**83453010**  
 Product:

CTP 5214 : AJOUT DIAM 14 ET COTE 3.1 MAX

Modified by F\_MONCHIAL 09/04/2002  
 Verified by R\_JUNILLON 09/04/2002  
 Authorized by



2, rue du Dr. ABEL  
 BP 59, 26902,  
 Valence CEDEX 9  
 France

Department:

CT

NATO code: FA0X2

Toler. gene. lin ±  
 Toler. gene. Ang ±

mm  
 degres

General  
 Raw surface  
 Ra ✓

*This document is the property of Crouzet-Automatismes.  
 It's contents cannot be reproduced or divulged without the company's written approval.  
 The product data and specifications found on this document  
 do not constitute any contractual obligation.  
 Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.  
 All rights of reproduction, modification, reprinting, and translation reserved for all countries.*



Scale  
**1/1**

Customer:

Customer Ref.:

Designation/FR:

**BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR BIPOLAIRE**  
**WATERPROOF PUSH-BUTTON TACTILE-EFFECT TWO-POLE CHANGE OVER**

PFT001:0<C>;0<M>

Designation/GB:

Dispatching **01**

Design by R\_JUNILLON 23/11/1993

Index **B**

Verif. by R\_JUNILLON 23/11/1993

Format **A4**

Authorized by

Folio **1/1**

DATA SHEET

**FT83453010FR**