



POUSSOIR NOIR

BLACK BUTTON

ENDURANCE MECANIQUE: 100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:

MECHANICAL STRENGTH: 100000 CYCLES
 WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-453-001

SPECIFIC ELECTRICAL CHARACTERISTICS	
VOLTAGE 28VCC	ELECTRICAL ENDURANCE
INDUCTIVE L/R 5ms	
I ≤ 2A ->	100 000 CYCLES
I ≤ 2,5A ->	80 000 CYCLES
I ≤ 3,5A ->	50 000 CYCLES

-
 -
83453012
 Product:

B	CTP 5214 : AJOUT DIAM 14 ET COTE 3.1 MAX		
	Modified by	F_MONCHIAL	09/04/2002
	Verified by	R_JUNILLON	09/04/2002
Authorized by			

Toler. gene. lin ± mm
 Toler. gene. Ang ± degres

General Ra
 Raw surface ✓

Crouzet
 2, rue du Dr ABEL
 BP 59, 26902,
 Valence CEDEX 9
 France
 Department: CT
 NATO code: FA0X2

Customer: **BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR BIPOLAIRE**
 Designation/FR: **WATERPROOF PUSH-BUTTON TACTILE-EFFECT TWO-POLE CHANGE OVER**
 Designation/GB: **DATA SHEET**

Design by R_JUNILLON 16/03/1995
 Verif. by R_JUNILLON 16/03/1995
 Authorized by

Dispatching **01**
 Index **B**
 Format **A4**
 Folio **1/1**

This document is the property of Crouzet-Automatismes.
 It's contents cannot be reproduced or divulged without the company's written approval.
 The product data and specifications found on this document do not constitute any contractual obligation.
 Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
 All rights of reproduction, modification, reprinting, and translation reserved for all countries.

Scale **1/1**

Customer Ref.: PFT001:0<C>;0<M>
 Dispatching **01**
 Index **B**
 Format **A4**
 Folio **1/1**

FT83453012FR