



POUSSOIR NOIR

BLACK BUTTON

ENDURANCE MECANIQUE: 100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:

MECHANICAL STRENGTH: 100000 CYCLES
 WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-453-001

SPECIFIC ELECTRICAL CHARACTERISTICS	
VOLTAGE 28VCC	
INDUCTIVE L/R 5ms	ELECTRICAL ENDURANCE
I ≤ 2A ->	100 000 CYCLES
I ≤ 2,5A ->	80 000 CYCLES
I ≤ 3,5A ->	50 000 CYCLES

-
 -
83453013
 Product:

B	CTP 5214 : AJOUT DIAM 14 ET COTE 3.1 MAX		
	Modified by	F_MONCHIAL	09/04/2002
	Verified by	R_JUNILLON	09/04/2002
Authorized by			

Toler. gene. lin ± mmm
 Toler. gene. Ang ± degres



General Ra
 Raw surface

2, rue du Dr. ABEL
 BP 59, 26902,
 Valence CEDEX 9
 France

Customer:
 Designation/FR: **BOUTON POUSSOIR COURT ETANCHE A EFFET TACTILE INVERSEUR BIPOLAIRE**
 Designation/GB: **WATERPROOF SHORT PUSH-BUTTON CHANGE-OVER TACTILE-EFFECT TWO-POLE**

Design by FERNANDES J 12/04/1996
 Verif. by R_JUNILLON 12/04/1996
 Authorized by

Dispatching **01**
 Index **B**
 Format **A4**
 Folio **1/1**

Department:

CT

Customer Ref.:

NATO code: FA0X2

FT83453013FR

Scale **1/1**



*This document is the property of Crouzet-Automatismes.
 It's contents cannot be reproduced or divulged without the company's written approval.
 The product data and specifications found on this document
 do not constitute any contractual obligation.
 Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications.
 All rights of reproduction, modification, reprinting, and translation reserved for all countries.*