

POUSSOIR ROUGE
 FORCE DE COMMANDE : 11.6 ± 1 N
 ENDURANCE MECANIQUE:100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:
 MIL STD 810 D-506.2 METHODE 2

RED BUTTON
 OPERATING FORCES : 11.6 ± 1 N
 MECHANICAL STRENGTH:100000 CYCLES
 WATERPROOF FRONT FACE IN COMFORMITY WITH:
 MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES.IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :


Sans homologation

FT83453001FR

Whitout homologation

SPECIFIC ELECTRICAL CHARACTERISTICS

VOLTAGE 28VCC INDUCTIVE L/R 5ms	ELECTRICAL ENDURANCE
$I \leq 2A \rightarrow$	100 000 CYCLES
$I \leq 2,5A \rightarrow$	80 000 CYCLES
$I \leq 3,5A \rightarrow$	50 000 CYCLES



-
-
83453023
Product:

B	CTP 6839 : FORCE DE COMMANDE 12.5 ± 0.7 N devient 11.6 ± 1 N	Modified by	JL_BOURGNE	21/09/2007
	FT83-453-001 devient FT83453001FR	Verified by	F_MONCHAL	21/09/2007
		Authorized by	Non Applic.	

Toler. gene. lin \pm	mm	<p>This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.</p>	
Toler. gene. Ang \pm	degrees		
	General Raw surface Ra \checkmark	Scale	1/1

2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France	Customer: HAL	Customer Ref.:	PFT001:0<C>;0<M>
Department: CT	Designation/FR: BOUTON POUSSOIR BIPOLAIRE ETANCHE + CACHE	Designation/GB: WATERPROOF PUSH-BUTTON GUARD CHANGE-OVER TACTILE EFFECT TWO-POLE	Dispatching D1
NATO code: FA0X2	Design by F_MONCHAL 13/01/2006	Verif. by A_BONNARD 13/01/2006	Authorized by Non Applic.
FICHE TECHNIQUE - DATA SHEET			Index Format Folio
FT83453023FR			B A4 1/1