

POUSSOIR COURT NOIR
 FORCE DE COMMANDE : 10.4 ± 0.8 N
 ENDURANCE MECANIQUE:100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:
 MIL STD 810 D-506.2 METHODE 2

BLACK SHORT BUTTON
 OPERATING FORCES : 10.4 ± 0.8 N
 MECHANICAL STRENGTH:100000 CYCLES
 WATERPROOF FRONT FACE IN COMFORMITY WITH:
 MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES.IDENTIQUE A :


OTHER CHARACTERISTICS IDENTICAL TO :

Sans homologation

FT83453001FR

Whitout homologation

SPECIFIC ELECTRICAL CHARACTERISTICS	
VOLTAGE 28VCC INDUCTIVE L/R 5ms	ELECTRICAL ENDURANCE
I ≤ 2A ->	100 000 CYCLES
I ≤ 2,5A ->	80 000 CYCLES
I ≤ 3,5A ->	50 000 CYCLES



-
-
83453024
Product:

B	CTP 6839 : FORCE DE COMMANDE 12.5±0.7N devient 10.4±0.8N	Modified by	JL_BOURGNE	21/09/2007
	FT83-453-001 devient FT83453001FR	Verified by	F_MONCHAL	21/09/2007
		Authorized by	Non Applic.	

Toler. gene. lin ± mm	This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.	
Toler. gene. Ang ± degrees		
	General Ra ✓ Raw surface	Scale 1/1

2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France	Customer: HAL	Customer Ref.:	PFT001:0<C>;0<M>		
	Designation/FR: BOUTON POUSSOIR BIPOLAIRE ETANCHE A EFFET TACTILE	Designation/GB: WATERPROOF PUSH-BUTTON CHANGE-OVER TACTILE EFFECT TWO-POLE		Dispatching 01	
Department: CT	Design by F_MONCHAL 16/01/2006	FICHE TECHNIQUE - DATA SHEET FT83453024FR		Index	Folio
NATO code: FA0X2	Verif. by A_BONNARD 16/01/2006			B	A4
	Authorized by Non Applic.				