

POUSSOIR NOIR
 FORCE DE COMMANDE : 11.6 ± 1 N
 ENDURANCE MECANIQUE:100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:
 MIL STD 810 D-506.2 METHODE 2

BLACK BUTTON
 OPERATING FORCES : 11.6 ± 1 N
 MECHANICAL STRENGTH:100000 CYCLES
 WATERPROOF FRONT FACE IN COMFORMITY WITH:
 MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES.IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :


Sans homologation

FT8345300IFR

Whitout homologation

SPECIFIC ELECTRICAL CHARACTERISTICS

VOLTAGE 28VCC INDUCTIVE L/R 5ms	ELECTRICAL ENDURANCE
$I \leq 2A \rightarrow$	100 000 CYCLES
$I \leq 2,5A \rightarrow$	80 000 CYCLES
$I \leq 3,5A \rightarrow$	50 000 CYCLES



-
-
83453029
Product:

A	Création de l'objet.	Modified by	T_VINARD	22/10/2008
		Verified by	A_BONNARD	22/10/2008
		Authorized by	NON APPLIC.	

Toler. gene. lin \pm	mm	<p>This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.</p>	
Toler. gene. Ang \pm	degrees		
	General Raw surface Ra <input checked="" type="checkbox"/>		Scale 1/1

2. rue du Dr ABEL BP 59, 26902. Valence CEDEX 9 France	Customer:	HAL ALH	Customer Ref.:	
Department:	Design by	T_VINARD 22/10/2008	FICHE TECHNIQUE - DATA SHEET FT83453029FR	
CT	Verif. by	A_BONNARD 22/10/2008	Index	Format
NATO code: FA0X2	Authorized by	NON APPLIC.	A	A4
				Folio 1/1