



POUSSOIR NOIR
 ENDURANCE MECANIQUE:100000 CYCLES
 ETANCHEITE FACE AVANT SUIVANT:
 MIL STD 810 D-506.2 METHODE 2
 AUTRES CARACTERISTIQUES.IDENTIQUE A :

BLACK BUTTON
 MECHANICAL STRENGTH:100000 CYCLES
 WATERPROOF FRONT FACE IN COMFORMITY WITH:
 MIL STD 810 D-506.2 METHODE 2
 OTHER CHARACTERISTICS IDENTICAL TO :

FT83-453-001

SPECIFIC ELECTRICAL CHARACTERISTICS	
VOLTAGE 28VCC	ELECTRICAL ENDURANCE
INDUCTIVE L/R 5ms	
I ≤ 2A →	
I ≤ 2.5A →	
I ≤ 3.5A →	100 000 CYCLES
	80 000 CYCLES
	50 000 CYCLES

-
 83453031
 Product:

A	Création du plan suite à IA2008029.	Modified by	T_VINARD	01/03/2010
		Verified by	B_TAILLET	01/03/2010
		Authorized by		

Toler. gene. lin ± 0.1 mm	<i>This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.</i>	
Toler. gene. Ang ± 3 degrees		
	General Ra ✓ Raw surface	Scale 1/1

2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France	Customer:	Customer Ref.:	PFT001:x<C>;y<M>			
	Designation/FR: BOUTON POUSSOIR BOMBE ETANCHE A EFFET TACTILE INVERSEUR BIPOLAIR	Designation/GB: WATERPROOF PUSH-BUTTON CHANGE-OVER TACTILE-EFFECT TWO-POLE		Dispatching	01	
Department: CT	Design by T_VINARD 01/03/2010	DATA SHEET		Index	Format	Folio
NATO code: FA0X2	Verif. by B_TAILLET 01/03/2010			A	A4	1/1
	Authorized by	FT83453031FR				