



Poussoir : Rouge
 Button : Red
 Endurance mécanique : 100000 Cycles
 Mechanical strenght
 Etanchéité face avant suivant : MIL STD 810 D-506.2 METHODE 2
 Waterproof front face according to

CARACTERISTIQUES ELECTRIQUES
ELECTRICAL CHARACTERISTICS

TENSION	28 Vdc	VOLTAGE
COURANT	0.1 mA à 500 mA	CURRENT
ENDURANCE ELECTRIQUE	100 000 cycles	ELECTRICAL LIFE

Autres caractéristiques identiques à : FT83453001FR
 Other characteristics identical to :

-
83453033
Product:

A	CREATION DE L'OBJET.	Modified by	T_VINARD	02/06/2010
		Verified by	P_GIROUD	02/06/2010
		Authorized by	NON APPLIC.	

Toler. gene. lin ± 0.1 mm	This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries	
Toler. gene. Ang ± 3 degrees		
	General Raw surface	Scale 1/1

2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France	Customer:	Customer Ref.:	PFT001:x<C>;y<M>		
	Designation/FR: BP BIP ETANCHE ROUGE COURT EFFET TACTILE CT DORE Designation/GB: RED SHORT WATERPROOF PUSH-BUTTON TACTILE EFFECT TWO POLE LOW CURRENT	DATA SHEET FT83453033FR		Dispatching	D1
Department: CT	Design by T_VINARD 02/06/2010 Verif. by P_GIROUD 02/06/2010	Index A Format A4 Folio 1/1			
NATO code: FA0X2	Authorized by NON APPLIC.				