



Poussoir : Noir
 Button : Black
 Endurance mécanique : 100000 Cycles
 Mechanical strenght
 Etanchéité face avant suivant : MIL STD 810 D-506.2 METHODE 2
 Waterproff front face according to

CARACTERISTIQUES ELECTRIQUES
 ELECTRICAL CHARACTERITICS

| | | |
|----------------------|-----------------|-----------------|
| TENSION | 28 Vdc | VOLTAGE |
| COURANT | 0.1 mA à 500 mA | CURRENT |
| ENDURANCE ELECTRIQUE | 100 000 cycles | ELECTRICAL LIFE |

Autres caractéristiques identiques à : FT83453001FR
 Other characteristics identical to :

| | | | | | |
|------------------------------|---|--|------------------------------------|-----------------------|------------------|
| A | CREATION DE L'OBJET | | Modified by | T_VINARD | 02/06/2010 |
| | | | Verified by | P_GIROUD | 02/06/2010 |
| | | Authorized by | | NON APPLIC. | |
| Toler. gene. lin ± 0.1 mm | | This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries. | | | |
| Toler. gene. Ang ± 3 degrees | | | | | |
| D | | General Raw surface | 1/1 | | |
| | 2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France | Customer: Designation/FR: BP BIP ETANCHE NOIR BOMBE CT OR Designation/GB: BLACK WATERPROOF PUSH-BUTTON TACTILE EFFECT TWO POLE LOW CURRENT | Customer Ref.: PFT001:x<C>;y<M> | Dispatching D1 | |
| Department: CT | Design by T_VINARD 02/06/2010 Verif. by P_GIROUD 02/06/2010 | DATA SHEET | | Index A | Format A4 |
| NATO code: FA0X2 | | FT83453034FR | | Folio 1/1 | |