



POUSSOIR NOIR

FORCE DE COMMANDE: 16N

FORCE DE RELACHEMENT: 3N MIN

ENDURANCE MECANIQUE: 1000 CYCLES

ETANCHEITE FACE AVANT SUIVANT:

MIL STD 810 D-506.2 METHODE 2

BLACK BUTTON

OPERATING FORCES: 16N

RELEASE FORCES: 3N MIN

MECHANICAL STRENGTH: 1000 CYCLES

WATERPROOF FRONT FACE IN CONFORMITY WITH:

MIL STD 810 D-506.2 METHODE 2

AUTRES CARACTERISTIQUES, IDENTIQUE A :

OTHER CHARACTERISTICS IDENTICAL TO :

FT83-453-501

-
-
83453510
Product:

A	CTP 5214 : AJOUT DIAM 14 ET COTE 3.1 MAX			Modified by	F_MONCHIAL	09/04/2002
				Verified by	R_JUNILLON	09/04/2002
				Authorized by		

Toler. gene. lin ± mm
Toler. gene. Ang ± degrees

General Raw surface Ra ✓

Crouzet
2, rue du Dr ABEL
BP 59, 26902,
Valence CEDEX 9
France
Department: CT
NATO code: FA0X2

Customer:
Designation/FR: **BOUTON POUSSOIR ETANCHE A EFFET TACTILE INVERSEUR BIPOLAIRE**
Designation/GB: **WATERPROOF PUSH-BUTTON TACTILE-EFFECT TWO-POLE CHANGE OVER**

Design by R_JUNILLON 16/03/1995
Verif. by R_JUNILLON 16/03/1995
Authorized by

Customer Ref.:
PFT001:0<C>;0<M>
Dispatching **D1**
Index **A** Format **A4** Folio **1/1**

DATA SHEET
FT83453510FR
Scale **1/1**
This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.