



POSITION 1 ACTIONNABLE AVEC LA PALETTE
POSITIONS 1 ET 2 ACTIONNEES PALETTE RELEVEE

POSITION 1 OPERABLE WITH THE GUARD
POSITIONS 1 ET 2 OPERABLE WHEN THE GUARD IS LIFTED UP

* Caract. GENERALES

- Temperature d'emploi
- Temperature de stockage
- Protection face avant
(MIL STD 810D/506-2/proced.II)
- Rigidite dielectrique
- Resistance d'isolement
- Masse
- Matiere

* GENERAL Caract.

- Ambient Temperature range -35° ↔ +75°C
- Storage Temperature range -55° ↔ +85°C
- Front face drip.proof
(MIL STD 810D/506-2/proced.II)
- Dielectric withstanding voltage 500V
- Insulation resistance >10MΩ sous 500Vcc
- Mass 27±2g
- Material Thermoplastique Inox
Thermoplast Stainless steel

* Caract. MECANIKES

- Couple de Commande FC
1er Circuit
2me Circuit
- Couple de relachement
- Course d'Approche
1er Circuit -> CA1
2em Circuit -> CA2
- Course Totale
- Couple de pivotement palette
- Vibrations Norme AIR 7306 Titre 3
Sinusoidales Fasci. 41 tabl. 2
Aleatoires Fasci. 42 Figure 17
- Endurance Mecanique

* MECANICAL Caract.

- Operate Torque FC
1st Circuit 0.3 N.m Max
2nd Circuit 0.5 N.m Max
- Release Torque 0.06 N.m Min
- Pre Travel
1st Circuit ->CA1 12° Max
2nd Circuit ->CA2 20° Max
- Total Travel 22° min
- Flap rotate torque 0.015 N.m Min
- Vibrations Air 7306 titre 3
Sinusoidal Part 41 Table 2
Random Part 42 scheme 17
- Mechanical Endurance 100 000 Cycles

* Caract. ELECTRIQUES

- Tension d'Alimentation
- Pouvoir de Coupure
En circuit resistif
En circuit selfique
- Endurance Electrique

* ELECTRICAL Caract.

- Nominal Voltage 30VDC ou 115VAC 400Hz
- Electrical Rating
Resistive circuit 6A
Inductive circuit L/R=5ms 3A
- Electrical Endurance 50 000 Cycles

83574509

Product:

D	CTP9489 : CORRECTION TEMPERATURE D'UTILISATION		Modified by	F_MONCHAL	27/04/2011
			Verified by	L_JULLY	27/04/2011
			Authorized by		
Toler. gene. Lin ± 0.1 mm		<p>This document is the property of Crouzet-Automatismes. It's contents cannot be reproduced or divulged without the company's written approval. The product data and specifications found on this document do not constitute any contractual obligation. Crouzet-Automatismes and its subsidiaries reserve the right to modify the specifications. All rights of reproduction, modification, reprinting, and translation reserved for all countries.</p>			
Toler. gene. Ang ± 1 degrees					
		General Raw surface R_a ✓		Scale 1/1	
2, rue du Dr ABEL BP 59, 26902, Valence CEDEX 9 France		Customer: Designation/FR: GACHETTE ETANCHE ROUGE 2 POSITIONS UNIPOLAIRE AVEC PALETTE Designation/GB: ONE POLE TWO POSITIONS TRIGGER MOMENTARY ACTION WITH GUARD		Customer Ref.: PFT001:<C>;<M> Dispatching 01	
Department: CT Design by R_JUNILLON 28/04/1997 Verif. by C_MARTIN 28/04/1997		FICHE TECHNIQUE - DATA SHEET FT83574509FR		Index	Folio
NATO code: FA0X2 Authorized by				D	A3 1/1